



Project \_\_\_\_\_  
 AIA # \_\_\_\_\_ SIS # \_\_\_\_\_  
 Item # \_\_\_\_\_ Quantity \_\_\_\_\_ C.S.I. Section 114000

## TBC-SERIES

### Undercounter Blast Chiller

### Self-Contained



### STANDARD PRODUCT FEATURES

- High Performance Refrigeration System
- Easy to Use Touch Screen Control with Automatic or Manual Operation
- Hands-Free Auto Start
- Adjustable Product Target Temps (40° to -5°F) or Cycle Times
- Four Chill Settings: Blast Chill, Speed, Energy Saving & Delicate
- On-Board Cycle Data Printer
- Three (3) Removable Food Probes for Multi-Batching
- USB Port, 90-Day Cycle Data Memory
- Stainless Steel Exterior & Interior
- Heavy Gauge Stainless Steel Work Top
- Long Life EZ-Clean™ Door Gasket(s)
- Five (5) Universal Type Trayslides (factory installed)
- Easy to Maintain Front Facing Condenser Coil
- Accommodates (5) 18" x 26" Pans or (10) 12" x 20" Pans

### ACCESSORIES & OPTIONS (\*field installed)

- Label Printer (adds "-LP" to device number)
- Set of Four (4) 3" or 4 1/8" Locking Casters
- Stainless Steel Back Option





Models listed to the applicable UL, CSA and NSF Standards by an approved NRTL. Consult the factory or unit data plate for additional information.

### AVAILABLE CONFIGURATIONS


Model	Hinging	Supports	Features
TBC5-50	R	6" Casters	Bullnose Worktop
TBC5-62	L	6" Casters	Bullnose Worktop
TBC5-52	R	6" Legs	Bullnose Worktop
TBC5-51	L	6" Legs	Bullnose Worktop
TBC5-63	R	4" Casters	Bullnose Worktop
TBC5-64	L	4" Casters	Bullnose Worktop
TBC5-66	R	3" Casters	Bullnose Worktop
TBC5-54	R	6" Casters	Bullnose Worktop, Stainless Steel Back
TBC5-58	L	6" Casters	Bullnose Worktop, Stainless Steel Back
TBC5-55	R	6" Legs	Bullnose Worktop, Stainless Steel Back
TBC5-65	R	4" Casters	Bullnose Worktop, Stainless Steel Back

Approved by \_\_\_\_\_ Date \_\_\_\_\_ Approved by \_\_\_\_\_ Date \_\_\_\_\_

MODEL  
TBC5



MODEL  
TBC5





**MODEL**

TBC5

**EQUIPMENT SPECIFICATIONS**

MODELS	TBC5
<b>DIMENSIONAL DATA</b>	
Net Capacity cu. ft.	9.2 (267 l)
L x D x H - Overall in. <sup>1</sup>	54 (137.2 cm) x 34 $\frac{1}{8}$ (88.8 cm) x 33 $\frac{3}{4}$ (85.7 cm)
Depth - over body in.	34 (86.4 cm)
Depth - door open 90° in.	58 $\frac{5}{8}$ (148.9 cm)
Clear door W x H in.	23 $\frac{1}{8}$ (58.7 cm) x 20 $\frac{3}{8}$ (69.9 cm)
No. Tray Slides	5
Pan Capacity	(5) 18" x 26"   (10) 12" x 20"
Product Capacity lbs.	100
<b>ELECTRICAL DATA</b>	
Voltage   Plug	115/60/1   NEMA 5-20P (attached)
Feed wires with ground	3
Full Load Amps   Req'd Circuit	16.0   20 Amp
<b>REFRIGERATION DATA</b>	
Refrigerant	R-448A
Refrigerant Charge Amt. oz	24 (680.4 gr)
BTU/HR   H.P. <sup>2</sup>	4400   3/4 HP
Required Clearance	n/a
<b>SHIPPING DATA</b>	
L x D x H Crated in.	66(167.6 cm) x 42 (106.6 cm) x 40 (101.6 cm)
Volume Crated cu. ft.	65 (1840.6 l)
Uncrated   Crated Weight lbs.	653 (296.1 kg)   713 (323.4 kg)

**NOTES:**

1. Height shown when mounted on standard 6" high legs or casters.
2. Based on a 90°F ambient and 0°F evaporator.

**ESTIMATED PERFORMANCE CHART**

TBC5 Product Load	Chill Time From 135°F to 40°F
50 (lbs.)	85
75 (lbs.)	140
100 (lbs.)	180

**CONSTRUCTION, HARDWARE, INSULATION**

Cabinet exterior and interior are constructed of stainless steel. The exterior cabinet back and bottom are constructed of heavy gauge galvanized steel. A heavy gauge stainless steel bull-nose work top is provided standard. Door is equipped with a cylinder lock and guaranteed for life self-closing cam-lift hinges with a stay open feature. Gasket profile and durable long life material simplify cleaning and increase overall gasket life. Anti condensate heaters are located behind the door opening. Both the cabinet and door are insulated with an average of 2" thick high density, non-CFC, 100% foamed in place polyurethane.

**SELF-CONTAINED REFRIGERATION SYSTEM**

A high-capacity, self-contained refrigeration system using environmentally friendly, non flammable R-448A refrigerant is coupled with an advanced air circulation system to rapidly chill hot food through the HACCP danger zone. It features a thermostatic expansion valve, high-humidity evaporator coil, high speed evaporator fan, air-cooled hermetic compressor, hot gas defrost and a non-electric condensate evaporator. The condenser coil is front facing for easy cleaning. Defrost occurs automatically, does not interrupt chill cycles in progress, nor starting new chill cycles, and intervals between defrost cycles are adjustable to better suit differing operational needs. A 9' cord and plug is provided.

**CONTROL / BASIC OPERATION**

The easy to use touch screen control is water resistant and protected from damage by a heavy gauge stainless steel bezel. Using the three probes provided, it monitors cycle progress and records all HACCP required data. This information can then be printed at the end of the cycle using the on-board printer and/or retrieved later from memory, where it is stored for 90-days.

Chill cycles can be started in one of two ways using either the AUTO (touch free) or MANUAL (fully adjustable) operating mode. In AUTO mode, placing any probe in 90°F or above product will initiate a chill cycle using the default parameters (standard blast chill with a target temperature of 37°F) in approximately 30-seconds. In MANUAL mode, the operator can adjust all the cycle parameters to suit their needs. Upon pressing START the chill cycle will commence using these inputs. Failure to complete cycle programming in MANUAL mode will result in the chill cycle starting automatically in 5-minutes after the last button push (provided at least one probe had been placed in product 90°F or above).

Product and/or user names can be manually input at the beginning or end of the chill cycle if desired. Customized chill cycle parameters (i.e. chill recipes) can be loaded and stored in advance, by name.

Once a chill cycle is started, it will continue without interruption until either the target temperature (using probes) or time (without using probes) is met. When using the default target temperature of 37°F, rapidly circulating air will cycle between 10-14°F or as low as -25°F when the target temperature is set at -5°.

Upon cycle completion, the blast chiller will notify the operator with an audible alarm, and automatically revert to maintenance mode, holding the product at the target temperature until removed.

**INTERIOR ARRANGEMENTS**

Standard interior arrangements include five (5) adjustable universal type tray slides, installed at the factory.

**DOMESTIC WARRANTY**

Both a six year parts and labor warranty and an additional one year compressor parts warranty (for a total of seven) are provided standard.