



Project \_\_\_\_\_  
 Item # \_\_\_\_\_ Quantity \_\_\_\_\_



**Stealth, Countertop, Portable  
 Induction Range**

Model #	Voltage	Peak Power	Plug Type
SM-181C-T (US)	110-120	1800 W	NEMA 5-15P

**Description:**

Spring USA's Stealth, Countertop, Portable Induction Range is a heating unit for product cooking or holding. The range features a low-profile design, titanium-colored stainless steel case, and integrated oversized pan support. Each range includes our exclusive SmartScan® technology with over/under voltage protection, pan size and pan type recognition, and large LED power/temp display.

**Construction & Performance Features:**

- Tempered, black, smoked glass faceplate
- Durable, stick-resistant, titanium finish, satin stainless steel body
- Rugged, 5 mm thick, easy to clean, tempered glass top
- 100% silicone rubber protective top seal
- Non-skid, non-scratch footing/base
- 7' power cord with plug
- Removable mesh air filter
- Simple, solid state controls
- Power ON/OFF heavy duty knob
- Power ON/Pan-Present indicator lights
- 'Cook' or 'Temp' mode
- 'Cook'/'Temp' mode touch pad control
- 'Cook'/'Temp' mode indicator lights
- Simple, knob-set thermostat control

- Lighted temperature indicator
- Power level 1-20 in 'Cook' mode
- Temperature range 110°F-400°F (43°C-204°C) in 'Temp' mode

**Standard Warranty:**

Spring USA Induction Ranges offer a one (1) year, overnight exchange warranty, from the date of invoice, against manufacturers defects. See SpringUSA.com for more details.

**Agency Listings:**

- ETL
- UL STD 197
- FCC
- CETL
- ETL-Sanitation to NSF-4



**Available Accessories/Alternate**

**Configurations:**

- Storage & Transport Box [Spring USA Catalog]
- Induction-ready Cookware and Serving Vessels [Spring USA Catalog]
- AF-350 Under-Counter Air Filter System
- Built-In, High Power Induction Ranges
- Custom Tabletop Induction featuring SmartStone®

Stealth, Countertop, Portable Induction Range

**Electric Requirements:**

Model #	Voltage	Phase	Hertz	Watts	Amps	Plug
SM-181C-T	110-120	1	60	1800	15.0	NEMA 5-15P

**Key Dimensions:**



Net Weight: 11.8 lb.

**Shipping Dimensions:**

Single Unit Shipping Carton			
Length	Width	Height	Weight
18.0"	15.5"	4.2"	13.0 lb.



Project \_\_\_\_\_  
Item # \_\_\_\_\_ Quantity \_\_\_\_\_

Stealth, Countertop, Portable Induction Range

### Notes & Conditions:

1. For optimum performance, allow 4" clearance from front and sides for good air circulation.  
**Proper ventilation must be provided at all times.**
2. Actual range temperature may vary due to a number of variables, such as ambient temperature in the immediate surrounding area, content and volume of food being heated or cooked, and whether or not you are using a cover on the serving vessel.
3. This induction range requires use of ferrous metal, induction-ready cookware.
4. Spring USA Induction Servers and Induction Warmers/Ranges are designed to work together as a system. Optimal performance is achieved by using Spring USA components in conjunction with each other. As the first to offer such induction systems, Spring USA cannot warranty the performance of facsimile products offered by other companies.